

# **Various** applications and options

Easybond Pin Brazing is ideally suited for many applications including continuity bonding between pipes, across flanges, connection of cathodic protection test and current carrying cables and connection of bracelet galvanic anodes etc.

The Easybond MKII equipment is very robust, easy to operate, easy to maintain and ideal for on site works.

# **The Easybond Pin Brazing Process**

The Easybond MKII is powered by a 36V DC battery pack (or suitable welding generator when using the generator gun) capable of delivering 240A for use with BAC fused brazing pins, ceramic ferrules and cable lugs.

With the earth device in place the gun trigger is depressed and after approximately 1.5 to 2 seconds the circuit is mechanically broken as the fuse wire breaks, and the brazing pin is held into the molten pool of brazing alloy that rapidly cools into a homogenous and very strong connection.

> "The safest, fastest simplest and most effective electrical bonding method available"

### **5 Easy Steps**



### **Benefits**

Speed of connection Takes around 60 seconds for 1 connection.

### **Low Temperature**

The low meting point (650°C) and short brazing time minimise the thermal effects on the steel.

#### **All Weather**

Pin brazing can be carried out in the wind rain or snow and damp conditions pose no problem.

#### Easy to use

Operators can be trained effectively to operate and maintain the equipment in less than one hour.

#### **Versatile**

Connections can be made at any orientation on a pipe.

#### Maintenance

Huge range of spare parts means easy onsite maintenance.







Trolley for Power Unit

EASYBOND MK II SYSTEM		
Part #	Description	
273 199 5660	Complete Easybond MK11 Brazing System (Including all the following components)	
273 199 5610	Power Unit for Easybond MKII complete with battery pack	
273 199 0780	Easybond Gun	L
270 071 5600	Pin holder for 8mm direct braze pins	
270 074 8150	Ferrule holder for 8mm direct braze pins	ľ
273 190 0610	Toolkit	ı
273 199 5020	Battery charger ELITE 110/230v supply	
273 190 1360	Earth device	
273 190 4680	Attaché case	L
278 900 1900	Manuals and training video on CD	

OPTIONAL ACCESSORIES FOR EASTBOND II	
Part #	Description
273 199 0685	Die Grinder, c/w 2 x 18V batteries, case and fitted with burr
273 190 1370	Grinding burr
273 199 5040	Battery charger 12V supply - In Car Charger
273 199 5640	Spare Battery Pack- sealed type, (c/w 3 x batteries, harness, connector & charge adaptor)
273 190 1460	Extension Cable 2.5m length
273 100 4825	Trolley for EBII Power Unit

GENERATOR BRAZING GUNS		
Part #	Description	
273 199 0240	Gun VF2300-ESAB c/w 8mm direct Pin &	
	Ferrule Holder	
273 199 5230	Gun VF2300 Extended c/w 8mm direct	
	Pin & Ferrule Holder	

Part #	Description
273 199 5100	Easybond Reach System (Including all
	the following components)
273 199 5060	Gun & Long Reach Extension c/w earth device
270 071 5600	Pin holder for 8mm Direct brazing pins
270 074 8150	Ferrule holder for 8mm direct braze pins
273 199 5070	Trigger Device
273 199 5090	Grinder Conversion Kit
273 900 0280	Grinding Disk Holder
273 900 0290	Grinding Disks (100 Pack)

tems also req	Juired that are common to Easybond U
73 199 5610 <sup>°</sup>	Battery Box unit for Easybond II
	complete with battery pack
73 199 0685	Die Grinder, c/w 2 x 18V batteries,
	case and fitted with burr
73 199 5020	Battery charger
	110/230v supply











Stingers

**BRAZING PINS WITH FUSE WIRE - 2** Description

8mm Direct Brazing Pin (Min Pack size 100)

270 083 3520 8mm Direct Brazing Pin Extra Solder B

(Min Pack size 100) 278 190 0430 M8 Threaded Brazing Pin (Pack size 50)

278 190 3450 M10 Threaded Brazing Pin (Pack size 40) 278 190 2560 M12 Threaded Brazing Pin (Pack size 40)

**FERRULES - 5** 

Part # Description

270 065 7230 Ceramic Ferrule 8mm for direct pins

(Pack size 100)

270 077 3680 Ceramic Ferrule 12mm for threaded pins

(Pack size 50)

**CABLE LUGS - SUITABLE FOR ALL 8MM DIRECT BRAZING PINS & FERRULE - 4** 

Description

278 100 7360 Cable lug 10mm² cable (Pack size 100) 278 100 9000 Cable lug 16mm² cable (Pack size 100)

270 088 7800 Cable lug 25mm² cable (Pack size 50)

278 100 7810 Cable lug 35mm² cable (Pack size 50) 270 088 7790 Cable lug 50mm<sup>2</sup> cable (Pack size 50)

278 100 9890 Cable lug # 6 - #8 AWG cable (Pack size 50)

278 100 8590 Sleeve 2.5mm² t/s 278 100 7360

(Pack size 100)

278 100 8750 Sleeve 4mm<sup>2</sup> t/s 278 100 7360

(Pack size 100)

278 100 9270 Sleeve 6mm<sup>2</sup> t/s 278 100 7360

(Pack size 100)

**CONNECTION KITS - STINGER - INDIVIDUAL & KITS - 3** Part #

Description

Stinger #12 AWG to suit 1 - 2.5mm² cable (Pack size 100) 2 hole 278 100 8012

278 100 8042 Stinger #10 AWG to suit 4 -

6mm² cable (Pack size 100) 2 hole 278 100 8050 Stinger #12 AWG kit comprising

2781008010 #12AWG Stinger (50), 2781903250 Brazing pin (50) &

2700657230 Ferrule (50).

(Pack size 50)

278 100 8060 Stinger #10 AWG kit comprising 2781008010 #10AWG Stinger (50),

2781903250 Brazing pin (50) &

2700657230 Ferrule (50).

(Pack size 50)

"All BAC brazing pins are manufactured to the highest standards to ensure a safe, consistent and reliable connection"









"All Easybond MK II equipment, consumables and spare parts are normally ex stock and ready for same day delvery at our UK facility and at authorised distributors worldwide"







## **Training**

In order to get the best from your Easybond equipment we would always recommend training for your operatives and technicians.

BAC and it's authorised importers/distributors offer a full training program covering the operation, maintanence and changing out of spare parts on the Easybond system that will be tailored to suit individual client requirements.

a BAC validated training certificate.

### **Service**

BAC and it's authorised importers/distributors offer a full service and repair capability for your Easybond equipment. BAC and selected importors/distributors carry a full and comprehensive range of spare parts so that we can turn around fully serviced and repaired equipment within a short time. All spare parts are ex works and can be sent out to the client immediately upon request.



